



Heavy

## ACDC X430 S3

ACX430

**Mid-cut safety shoe with heat-resistant outsole and unique AC/DC branding**

The X430 safety shoes with unique AC/DC branding combine top safety features with comfort. Cold insulated, waterproof, metal free and heat resistant, they're perfect for various industries and environments.

Upper	Leather
Lining	Membrane
Footbed	SJ foam footbed
Midssole	Anti-puncture Textile
Outsole	PU/Rubber (NBR)
Toecap	Composite
Category	S3 / ESD, SRC, WR, CI, HRO
Size range	EU 36-50 / UK 3.5-14.0 / US 4.0-15.0 JPN 22.5-33.0 / KOR 235-330
Sample weight	0.780 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



112



124



**Waterproof (WR)**  
Waterproof footwear prevents liquids to enter into the shoe.



**DGVU BGR 191**  
These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.




**Heat resistant outsole (HRO)**  
The outsole resists high temperatures up to 300°C.



**Cold insulated (CI)**  
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



**Electrostatic Discharge (ESD)**  
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



**Metal free**  
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

**Industries:**

Construction, Automotive, Chemical, Cleaning, Logistics, Mining, Oil & Gas

**Environments:**

Uneven surfaces, Wet environment, Warm surfaces, Dry environment, Muddy environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	7.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	64	≥ 15
<b>Lining</b>	<b>Membrane</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	2.4	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	23	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	75	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.44	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	16.4	0.1 - 1000
	ESD value	MegaOhm	52	0.1 - 100
	Heel energy absorption	J	31	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.