



Heavy

ALASKA S3

Leather safety boot with warm lining

The Safety Jogger ALASKA are versatile leather safety boots with superior SR, warm lining, and cold insulation. They offer antistatic, water-resistant features and provide comfort with body posture pain relief and enhanced grip.

Upper	Pull-up Action Leather
Lining	Teddy
Footbed	Teddy
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SRC, CI
Size range	EU 38-47 / UK 5.0-12.0 / US 5.5-13.0 JPN 24-31 / KOR 250-310
Sample weight	0.804 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BRN



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Warm lining
Keeps your feet warm and dry in cold environments.



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

Industries:

Automotive, Chemical, Construction, Mining, Oil & Gas, Industry

Environments:

Cold environment, Muddy environment, Snowy and icy, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Pull-up Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	7.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	64	≥ 15
Lining	Teddy			
	Lining: permeability to water vapor	mg/cm ² /h	1206	≥ 2
	Lining: water vapor coefficient	mg/cm ²	964.8	≥ 20
Footbed	Teddy			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	85.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	108.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.