



Light

CAMILLE 01

Ultra-comfortable shoe made of Lycra

The CAMILLE shoes are made of Lycra and provide superior comfort and safety. Their features include SR slip resistance, electrostatic discharge, removable footbed. Perfect for demanding industries and vegan-friendly.

| | |
|---------------|--|
| Upper | Synthetic Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | Phylon/Rubber (NBR) |
| Category | O1 / ESD, SRC |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.243 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



LGN



BLK



FUC



LBL



LLC




WHT



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.

Industries:

Medical, Catering, Cleaning, Food & beverages

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.4 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 15.5 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 43.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 350 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 75 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.36 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.37 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.24 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.31 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 38 | 0.1 - 100 |
| | Heel energy absorption | J | 26 | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.