

Medium

FLOW S3 MID TLS

FLOWS3MTLS

Metal-free, mid-cut S3 safety shoe with ESD and TLS (Twist Lock System) closure

Metal-free version of our CADOR S3 safety shoe. FLOW S3 is SRC slip resistant and features ESD, a composite toe, a puncture-resistant midsole and many more benefits. With our game-changing Twist Lock System closure, you simply need to twist and lock to tighten these safety shoes in a flash! Water resistant and perfect for wet or dry environments.

| | |
|---------------|---|
| Upper | Synthetic Nubuck |
| Lining | 3D-Mesh |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | PU/PU |
| Toecap | Composite |
| Category | S3 / ESD, SRC |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.629 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |




BLK



TLS (Twist Lock System)

Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Airblaze technology

Moisture and temperature management system to provide optimum wearer comfort by keeping your feet dry and comfortable.



Puncture resistant lightweight

Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



Individual orthopedic solutions (Neskrid)

Do you have special needs for your feet? Thanks to our collaboration with Neskrid, it is possible to replace the original footbed with an individual orthopedic footbed that is certified for this particular shoe.

Industries:

Assembly, Automotive, Food & beverages, Industry, Logistics

Environments:

Dry environment, Wet environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Synthetic Nubuck | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 28 | ≥ 15 |
| Lining | 3D-Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 61.1 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 490 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 84 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.36 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.37 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 39 | 0.1 - 100 |
| | Heel energy absorption | J | 27 | ≥ 20 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 19.0 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.