



Medium

## ISIS S3

Mid-cut safety shoe in nubuck, designed for ladies

Safety Jogger ISIS is a ladies' safety shoe offering slip resistance, a composite toecap, water-resistant upper, and puncture resistance. Provides comfort, dry feet, and protection in various industries.


Upper	Nubuck Action Leather
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	Rubber (NBR)
Toecap	Composite
Category	S3 / SRC, HRO
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.478 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



210



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



**Metal free**  
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



**Composite toecap**  
Metalfree and lightweight, no thermal or electrical conductivity



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Water resistant Upper (WRU)**  
Prevents penetration of water if not permanently exposed to high levels.



**SJ Flex**  
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

**Industries:**

Automotive, Cleaning, Construction, Logistics, Industry

**Environments:**

Dry environment, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nubuck Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	27.3	≥ 15
<b>Lining</b>	<b>3D-Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	86.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	695.4	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	82.6	≤ 150
	Outsole slip resistance SRA: heel	friction	0.34	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.36	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.22	≥ 0.18
	Antistatic value	MegaOhm	24.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	24	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.