



**SAFETY  
JOGGER**  
PROFESSIONAL



Light

**JULIA OB**

JULIA2


**Professional and stylish work shoe**

The JULIA are the ideal work shoes for people who need a professional and stylish look without sacrificing comfort and safety. These shoes have a slip-resistant outsole with extra cushioning and a water-resistant leather upper, so you can work with confidence and keep going all day long.


Upper	Synthetic Leather
Lining	Mesh, Synthetic Leather
Footbed	SJ foam footbed
Outsole	PU/Rubber (NBR)
Category	OB / SRC, E, FO
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.235 kg
Norms	EN ISO 20347:2012



BLK



**Oxygrip / SJ Grip**  
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



**Breathable upper**  
Increased moisture and temperature management for extended wearer comfort.



**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED  
IN EUROPE**

www.safetyjogger.com

**Industries:**

Catering, Uniform

**Environments:**

Dry environment

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	31	≥ 15
<b>Lining</b>	<b>Mesh, Synthetic Leather</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	33.03	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	264	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	115	≤ 150
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.45	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.33	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.38	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	27	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.