



SAFETY JOGGER

PROFESSIONAL



Heavy

MICKEY SONIC OB

MICSONIC

Extremely light hospital clog with Mickey print

Upper	Expanded EVA
Lining	N/A
Footbed	N/A
Outsole	EVA
Category	OB / ESD, A, SRC, E
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.150 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



WHT



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



Hygienic waterproof solution

This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Cleaning, Medical

Environments:

Wet environment, Dry environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Expanded EVA			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Lining	N/A			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20
Footbed	N/A			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	EVA			
	Outsole abrasion resistance (volume loss)	mm ³	152	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.34	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.17	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.20	≥ 0.18
	Antistatic value	MegaOhm	0.69	0.1 - 1000
	ESD value	MegaOhm	0.07	0.1 - 100
	Heel energy absorption	J	47	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.