



PRO IMPACT 4X42CP

PROIMPACT

Gloves with impact protection

The Safety Jogger PRO IMPACT gloves offer unparalleled safety with advanced impact protection. Perfect for assembly, automotive, industry, and construction environments. Experience superior protection.

Performance level	4X42CP
Liner	13 GAUGE HPPE
Coating	FOAM NITRILE
Category	TSF-Touchscreen function
Size range	EU 7-11
Sample weight	0.081 kg
Norms	EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



Industries:

Automotive, Assembly, Construction, Industry



514

Performance level 4X42CP

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.