



## PROIMPACT SINGLE 4X42CP

PROIMPACTS

**Veiligheidshandschoenen met impactbescherming**

The Safety Jogger PRO IMPACT gloves offer unparalleled safety with advanced impact protection. Perfect for assembly, automotive, industry, and construction environments. Experience superior protection.

Performance niveau	4X42CP
Liner	13 GAUGE HPPE
Coating	FOAM NITRILE

13G

**Industrieën:**

Automobielsector, Montage, Bouw, Industrie



514

## Performance niveau 4X42CP

EN388:2016	0	1	2	3	4	5
a. Schuurweerstand (toeren)	< 100	100	500	2000	8000	-
b. Snijweerstand (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Scheursterkte (Newton)	< 10	10	25	50	75	-
d. Steekweerstand (Newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Steekweerstand recht lemet (Newton)	2	5	10	15	22	30

- a. Schuurweerstand: gebaseerd op het aantal cycli dat nodig is om door de monsterhandschoen te wrijven.
- b. Snijweerstand: gebaseerd op het aantal cycli dat nodig is om met een draaiend mes met een constante snelheid door het monster te snijden.
- c. Scheurweerstand: gebaseerd op de hoeveelheid kracht die nodig is om het monster te scheuren.
- d. Prikweerstand: gebaseerd op de hoeveelheid kracht die nodig is om het monster te doorboren met een punt van standaardformaat.
- e. Snijweerstand volgens TDM100 test: gebaseerd op het aantal cycli dat nodig is om met een glijdend mes met een constante snelheid door het monster te snijden.