



Medium

TACTIC OB

Mid-cut allround tactical boot

High-cut allround tactical leather boot made for tactical purposes. With it's 562 grams it's an extreme lightweight tactical boot.

| | |
|---------------|---|
| Upper | Nappa Action Leather, Textile |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | Rubber (NBR) |
| Category | OB / SRA, FO, HRO |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.632 kg |
| Norms | ASTM F3445:2021 EN ISO 20347:2012 |




SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



BLK

Industries:

Tactical, Uniform

Environments:

Muddy environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|---|--------------|-------------|--------------|
| Upper | Nappa Action Leather, Textile | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 4.5 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 35 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 45 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 350 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 85 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.28 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.32 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | N/A | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | N/A | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | N/A | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com