



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1562/161/02/21/0291

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : **CORTINA NV**
Meersbloem-Melden 42, B-9700 Oudenaarde
Belgium

Description

PPE Type : *overshoe of protection against impact, compression and slip resistance*

Product reference : **VISITOR METAL FREE**

Construction and material of outsole : **Rubber part manufactured in one piece by compression and a glued toecap.**

Pictures :



VISITOR METAL FREE

O/107667 SIZE M – Q3/2020



Meersbloem-Melden 42

B-9700 Oudenaarde

BELGIUM

MADE IN CHINA

Reference standard : **Expert statement based on the protocol CTC CE C 005**

Size range : **S (34-38) – M (38/43) – L (43/48+)**

Toecap nature : **Non Metallic**

Insert nature : **N/A**

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 03 dated from FEBRUARY 2022 and the Instruction for Use index V1, 23 Feb., 2022.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by

Didier GUISADO

Certification and Quality Manager

Date of first issue : 15 February 2021

End of validity date : 13 october 2025

Update 02 : 28 February 2022



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

CORTINA NV

MANUFACTURER'S TECHNICAL FILE

Reference of the product : VISITOR METAL FREE

Article code : /

Technical file index : 03

Last update : FEBRUARY, 2022

IDENTIFICATION

Reference of the product : VISITOR METAL FREE
Article Code : /
Basic model
Technical file index : 03
Last update : FEBRUARY, 2022

Manufacturer :

CORTINA NV

Meersbloem-Melden 42, B-9700 Oudenaarde

Belgium

tel : 00 32 55 33 57 05

fax :

Factory :

Hua Feng Rubber Plastic Products Co Ltd

Han Xi Shui Industrial Quarter Cha Shan - Dong Guan City

CHINA

Tel : 0086-769 -86413540

Fax : 0086-769-86413211

Dongguan Gaobu Lyter Safety Shoes Materials Factory

N° 28-1 East centre Road, Gaobu Twon , Dongguan, Guangdong.china.

CHINA

Tel : 0086 134 1271 8700 (SUSI WANG)

Authorised Representative :

CORTINA NV

MEERSBLOEM-MELDEN 42, B-9700 OUDENAARDE

BELGIUM

tel: 0032 55 33 57 05

fax:

website : www.safetyjogger.com

FOOTWEAR DESCRIPTION

Footwear description:

Overshoe to protect against falling objects on the toes impact and compression risks and slip resistance.

Visual description:

General view :

Outsole view :



Reference of the mould : MVMFTG02.2020

Range of sizes :

S (34-38) – M (38/43) – L (43/48+)

Construction and material of outsole :



Rubber part manufactured in one piece by compression and a glued toecap.

Field of use

Overshoe used for factory visits, airport areas, which requires protecting the feet (toes) from crushing, shocks and slipping. The characteristic of this overshoe: it is metal-free.

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Expert statement
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Expert statement
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Expert statement
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.14	Multi-risk PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Expert statement
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking

FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	TVITG1.11	Caoutchouc	Noir
OUTSOLE	SVITG1.11	Caoutchouc	Noir
TOE CAP	ROE MF 7/11/12	Fibre de verre	Grise
DECORATIVE ELEMENTS		Attache en PU thermo-soudé et cousu à du velcro (mâle et femelle)	Noir
		Becquet de 3 couleurs différentes sur la coque pour indiquer la taille de la surchaussure	Bleu, rouge et vert

PROTECTION SCOPE

Basic requirements :

This product has been designed to be a safety overshoe

Compliance with the essential requirements of the Regulation 2016/425 has been verified by "expert statement" and by using following technical rules :

Protocol CTC CE C 005 based on requirements of standard EN ISO 20345:2011 and innocuousness

5.3.2.1 toecap generalities

5.3.2.2 internal length of toecap

5.3.2.3 impact (200 J)

5.3.2.4 compression (15 KN)

5.3.2.5 behaviour of toecap (*non-metallic*) (EN12568:2010)

5.3.4 ergonomoy

5.3.5 slip resistance flat requirement concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol

5.4.2 Thickness of the upper

5.4.4 tensile properties of the upper

5.4.5 Flexing resistance of the upper

5.8.1.1 thickness (cleated outsole)

5.8.1.2 cleated area

5.8.1.3 cleat height

5.8.2 tear strength

5.8.3 abrasion

5.8.4 rigidity / flexing resistance

6.4.2 Resistance to fuel oil

organo-tins on outsole

PAH on rubber

At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (n° 1907/2006 and revisions)

It is a category II product

MARKING - PACKAGING

Information printed on the footwear :

- * Logo of the Manufacturer
- * Logo **CE**
- * Manufacturer's type designation
- * Postal address of manufacturer
- * Footwear's reference VISITOR METAL FREE
- * Article code /
- * Size
- * Year of manufacture and at least quarter
- * The number and year of the Standard used
- * The symbol(s) of the additional requirements

Marking example :

CE
VISITOR METAL FREE
O/107667 SIZE M – Q3/2020

Meersbloem-Melden 42
B-9700 Oudenaarde
BELGIUM
MADE IN CHINA

The location of marking is : Marking inside each foot

Method of marking on the footwear :

Included in the mould

Packaging :

Each pair is packed in a nylon bag with drawstring

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	Reference
CTC	L200304403_1
CTC	L200304425_2
CTC	L200304450_1

MEANS OF CONTROL

1. Inspection/testing of incoming materials based on the applicable standard : 2,5%
2. Inline inspection/testing of all relevant safety and quality properties based on the applicable standard:
 - Tensile Strength test: 2 pcs per day in different sizes
 - Impact Resistance and Compression Resistance test: 1 pair per day in different sizes
 - Slip resistance: 2 pairs per day in different sizes
 - Fuel Oil Resistance Test: 1 pcs in different size per 1500 pairs
3. Final random inspection/testing at the end of production based on the applicable standard based on AQL 2,5

PPE subject to ageing :

Peremption period : 7 years when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : <http://dw.safetyjogger.com/?dir=certificates/>