

SAFETY JOGGER

INDUSTRIAL

CLASSICS

A210 S1P

Perforated, low-cut safety shoe for optimal ventilation


Upper	Waterproof Suede
Outsole	PU/PU
Toecap	Steel
Midssole	Steel
Lining	Mesh
Footbed	Mesh
Safety category	EN ISO 20345 - S1P / SRC
Sample weight	0.550 gr.
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 / CM 23.5-31.5



S1P
You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



STEEL TOECAP
Robust metal support to protect the feet of the wearer against falling or rolling objects.




STEEL MIDSOLE
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



SJ FLEX
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



BREATHABLE LEATHER UPPER
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



HEEL ENERGY ABSORPTION
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

SAFETY JOGGER

INDUSTRIAL

CLASSICS

A210 S1P

Industries:

Automotive, Construction, Food & beverages, Industry, Logistics

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Waterproof Suede			
	Upper: permeability to water vapor	mg/cm ² /h	0.88	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	16.5	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	2.2	≥ 2
	Lining: water vapor coefficient	mg/cm ²	22	≥ 20
Footbed	Mesh			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	225	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.35	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.19	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	565	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	22	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41