



#

AAK S1P LOW S1 PS

AAKS1PLOW

##

#####. ### ## # AAK S1P ##### ## ## ## ##
#####. ### ## # ##### ## ## ## ESD# #####.

## #	##, ##
## #	### #
##	SJ ### #
##	## ##
## #	###/##
Top	##
####	S1 PS / SR, ESD, FO, HRO
## #	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## #	0.480 kg
###	ASTM F2413:2018 EN ISO 20345:2022



BLU



BLK



DBL




GRY



#####.



##(SR)
SRA+SRB=SRC ##
#####. SR# ##### ## ## ##
#####.



##, ## # ##, ##
##, ## # ## ## ##


#####.



##.
100% ## ## ## ##.



##.



#####. ## ## ## ## # ##
##.

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
####, ###, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##			
	##: ### ###	mg/cm²/h	1.2	# 0.8
	##: ### ##	mg/cm²	21	# 15
## ##	### ##			
	##: ### ###	mg/cm²/h	34.59	# 2
	##: ### ##	mg/cm²	277	# 20
##	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	### #####(## ##)	mm³	119.4mm³(Density:1.3)	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.48	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.48	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.36	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.36	# 0.22
	### ## #	###	650	0.1 - 1000
	ESD #	###	21.9	0.1 - 100
	#### ## ##	J	25	# 20
Top	##			
	#### ## ##(## # ## 100J)	mm	NA	N/A
	#### ## ##(## # ## ## 10kN)	mm	NA	N/A
	#### ## ##(## # ## 200J)	mm	16.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	22.0	# 14

##:

###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ##### ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com