



###

ALASKA S3

#####

#####

####	#####
##	##
####	##
#####	##
#####	##PU/##PU
#####	##
#####	S3 / SR, SC, ##, #####, #####
#####	EU 38-47 / UK 5.0-12.0 / US 5.5-13.0
#####	JPN 24-31 / KOR 250-310
#####	0.804 kg
##	ASTM F2413:2018
	EN ISO 20345:2022+A1:2024



S3
S3#####
#####



SRC#####
#####1##
##SRC##SRA#SRB##

#####



#####CI#
#####CI#####
##



#####



#####WRU#

#####



#####100 KiloOhm##1 GigaOhm
#####



BRN

####:

#####, ####, ##, ##, #####, ####

#####:

##, ##, ##, #####, ####

#####:

#####

####		####	##	EN ISO 20345
####	#####			
	#####	mg/cm²/h	1.5	# 0.8
	#####	mg/cm²	16.8	# 15
##	##			
	#####	mg/cm²/h	47.5	# 2
	#####	mg/cm²	379.8	# 20
####	##			
	#####	####	25600/12800	25600/12800
#####	##PU/##PU			
	#####	mm³	33	# 150
	- #####NaLS - #####	#####	0.44	# 0.31
	- #####NaLS - #####	#####	0.41	# 0.36
	SR ## - ##### - #####	#####	0.30	# 0.19
	SR##### - ##### - #####	#####	0.31	# 0.22
	#####	#####	40.1	0.1 - 1000
	ESD#	#####	N/A	0.1 - 100
	#####	J	30	# 20
#####	##			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	18.5	# 14
	#####15kN#	mm	21.0	# 14

####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com