



# SAFETY JOGGER

PROFESSIONAL



Light

## ALIZA OB

### Vegan ESD Sandal Lycra

ALIZA sandals offer ESD protection, elastic fit, orthopedic insole support, and slip-resistant comfort. Perfect for medical, catering, and food industries.

|               |                                                                    |
|---------------|--------------------------------------------------------------------|
| Upper         | Lorica                                                             |
| Lining        | Recycled Mesh                                                      |
| Footbed       | SJ foam footbed                                                    |
| Outsole       | Phylon/Rubber (NBR)                                                |
| Category      | OB / ESD, A, SRC, E                                                |
| Size range    | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.250 kg                                                           |
| Norms         | ASTM F2892:2018<br>EN ISO 20347:2012                               |



LBL



WHT



FUC



LLC



LMG



#### Stretchable upper

Super elastic and stretchable textile for improved comfort and fit.



#### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



#### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY JOGGER  
WORKS

HEAD-TO-TOE  
PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description                                     | Measure unit | Result      | EN ISO 20347 |
|---------|-------------------------------------------------|--------------|-------------|--------------|
| Upper   | Lorica                                          |              |             |              |
|         | Upper: permeability to water vapor              | mg/cm² /h    | 27.6        | ≥ 0.8        |
|         | Upper: water vapor coefficient                  | mg/cm²       | 221         | ≥ 15         |
| Lining  | Recycled Mesh                                   |              |             |              |
|         | Lining: permeability to water vapor             | mg/cm² /h    | 40.4        | ≥ 2          |
|         | Lining: water vapor coefficient                 | mg/cm²       | 325         | ≥ 20         |
| Footbed | SJ foam footbed                                 |              |             |              |
|         | Footbed: abrasion resistance (dry/wet) (cycles) | cycles       | 25600/12800 | 25600/12800  |
| Outsole | Phylon/Rubber (NBR)                             |              |             |              |
|         | Outsole abrasion resistance (volume loss)       | mm³          | 118         | ≤ 150        |
|         | Outsole slip resistance SRA: heel               | friction     | 0.37        | ≥ 0.28       |
|         | Outsole slip resistance SRA: flat               | friction     | 0.37        | ≥ 0.32       |
|         | Outsole slip resistance SRB: heel               | friction     | 0.19        | ≥ 0.13       |
|         | Outsole slip resistance SRB: flat               | friction     | 0.23        | ≥ 0.18       |
|         | Antistatic value                                | MegaOhm      | N/A         | 0.1 - 1000   |
|         | ESD value                                       | MegaOhm      | 51          | 0.1 - 100    |
|         | Heel energy absorption                          | J            | 28          | ≥ 20         |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com