



**SAFETY
JOGGER**
INDUSTRIAL



ALLFLEX 4131A

ALLFLEX ##### Safety Jogger #####

#####

#####	4131A
###	#### + ##### 15 ###
#####	#####
#####	SIF #####
#####	EU 6-12
#####	0.020 kg
#####	ANSI/ISEA 105:2016
	EN ISO 21420:2020
	EN 388:2016



EN ISO 21420

EN 388:2016



#####:
#####, #####, #####, #####,
#####, #####, #####, #####, #####,
####, #####

EN 388



174

4131A

EN388:2016	0	1	2	3	4	5
a. ##### (###)	< 100	100	500	2000	8000	-
b. ##### (#####)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. ##### (#####)	< 10	10	25	50	75	-
d. ##### (#####)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. ##### (#####)	2	5	10	15	22	30

- a. #####: #####
- b. #####: #####
- c. #####: #####
- d. #####: #####
- e. ##### TDM100: #####

#####

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com