

ALLFLEXDOT 12PACK 4131A

ALLFLEXDOP

Precision Gloves 12Pack

ECO ALLFLEXDOT gloves provide agility and sensitivity for light assembly. Foam nitrile dots deliver superior grip, comfort, and control in dry conditions.

4131A
15 Gauge/Polyamide/Spandex
Foam Nitrile/ Nitrile Dots
TSF-Touchscreen function, SIF-Silicone Free
EU 6-12
0.021 kg
EN ISO 21420:2020 EN 388:2016



















BLK

EN ISO 21420





EN 388:2016

Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Performance level 4131A

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	<100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	В	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

Touchscreen compatible

You can use your smartphone or tablet without taking off the gloves, thanks to their special coating.

DMF-free PU

Made from polyurethane that doesn't contain DMF (a chemical that can be harmful), which means they are safe to use.



