



SAFETY JOGGER

INDUSTRIAL

ALLFLEXDOT 4131A

#####

Safety Jogger ALLFLEXDOT

#####	4131A
###	##### 15 ###
#####	##### / #####
#####	##### TSF, SIF #####
#####	#####
#####	EU 7-11
#####	0.021 kg
#####	ANSI/ISEA 105:2016
	EN ISO 21420:2020
	EN 388:2016



EN ISO 21420

EN 388:2016



#####:



BLK

4131A

EN388:2016	0	1	2	3	4	5
a. ##### (###) (&###)	< 100	100	500	2000	8000	-
b. ##### (###) (###)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. ##### (###)	< 10	10	25	50	75	-
d. ##### (###) (###)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. ##### (#####) (#####)	2	5	10	15	22	30

- a. #####: #####
 - b. #####: #####
#####
 - c. #####: #####
 - d. #####: #####
#####
 - e. ##### TDM100: #####

#####

#####

Proudly ranked in the
top 1% by EcoVadis
for sustainability



HEAD-TO-TOE PROTECTION



**ENGINEERED
IN EUROPE**

**SAFETY
JOGGER
WORKS**

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com