



Heavy

ALTAR S3 MID S3S

ALTARS3MID

##

S3 ## ## ## (Safety Jogger)# #### ##### #####. SR ### ##,
##, ## ## ##, #### ## ##, ## ## ##, ## ## ##, ## ## ## ## ## ##.


## ##	#### ## ##
## ##	### ##
##	SJ # ##
##	## ## ##
## #	PU/##
Top	##
####	S3S / SR, SC, LG, ESD, ##, CI, FO, HRO
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.804 kg
###	ASTM F2413:2018 EN ISO 20345:2022



##.




##.




##.



300°C# ## ## ## ## ##.



##.



#####. ## ## ## ## ## ## ## ## ## ##
##.



CAM



SND

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
##, ##, ##, ###

##:
##, ### ##, ## ##### ##, ### ##, ### ## ##, ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ## ##			
	##: ### ##	mg/cm²/h	7.8	# 0.8
	##: ### ##	mg/cm²	68	# 15
## ##	### ##			
	##: ### ##	mg/cm²/h	54.48	# 2
	##: ### ##	mg/cm²	436	# 20
##	SJ # ##			
	###: ###(##/##)(###)	##	25600/12800	25600/12800
## #	PU/##			
	### ####(## ##)	mm³	91	# 150
	## ### ## - ### + NaLS - ## ### ####	##	0.41	# 0.31
	## ### ## - ### + NaLS - ## ## ##	##	0.37	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.28	# 0.19
	SR ### ## - ### + ##### - ## ## ##	##	0.25	# 0.22
	### ## #	###	11.2	0.1 - 1000
	ESD #	###	65	0.1 - 100
	#### ## ##	J	33	# 20
	##			
Top	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	17.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	21.5	# 14

#: 42

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com