



Heavy

APOLLO S5

PVC Steel Toe Safety Boots

Safety Jogger APOLLO safety boots combine strong steel protection with comfort. Antistatic, oil-resistant, and shock-absorbing for safe, all-day performance.

Upper	SJ PVC
Lining	Tricot
Footbed	N/A
Midsole	Steel
Outsole	PVC
Toecap	Steel
Category	S5 / FO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	1.100 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



YEL



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Seamless upper construction

Optimized wearer comfort due to missing overlappings that can cause pressure points.

Industries:

Catering, Cleaning, Construction, Food & beverages, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	SJ PVC			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	# 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	# 15
Lining	Tricot			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	# 2
	Lining: water vapor coefficient	mg/cm ²	N/A	# 20
Footbed	N/A			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	N/A	25600/12800
Outsole	PVC			
	Outsole abrasion resistance (volume loss)	mm ³	162	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.36	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.37	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	# 0.22
	Antistatic value	MegaOhm	201	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	20	# 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	24.0	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	24.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.