

Heavy

## ARAS S3

### Composite Toe Work Boots With Cold Insulation

Safety Jogger ARAS leather safety shoes keep feet warm and protected. Cold-insulated and flexible midsole for comfort in cold environments.

Upper	Nappa Action Leather
Lining	3M Thinsulate
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Composite
Category	S3 / ESD, SRC, CI
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.705 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



#### Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.




#### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



#### Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

**Industries:**  
Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry

**Environments:**  
Cold environment, Dry environment, Extreme slippery surfaces, Muddy environment, Snowy and icy, Uneven surfaces, Warm surfaces, Wet environment

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	2	# 0.8
	Upper: water vapor coefficient	mg/cm²	25.5	# 15
Lining	<b>3M Thinsulate</b>			
	Lining: permeability to water vapor	mg/cm²/h	21.6	# 2
	Lining: water vapor coefficient	mg/cm²	173	# 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	41	# 150
	Outsole slip resistance SRA: heel	friction	1.35	# 0.28
	Outsole slip resistance SRA: flat	friction	0.37	# 0.32
	Outsole slip resistance SRB: heel	friction	0.13	# 0.13
	Outsole slip resistance SRB: flat	friction	0.18	# 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	79	0.1 - 100
	Heel energy absorption	J	31	# 20
Toecap	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	23	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



[www.safetyjogger.com](http://www.safetyjogger.com)