



#####

ASAMA S3S MID TLS

ASAMAS3MTL

TLS#####

Safety Jogger ASAMAS3MTL#####TLS###
#####ESD#####

#####, #####


SJ#####

#####/##

S3S / SR, ESD, #####, #####, #####, HRO
EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
JPN 21.5-31 / KOR 230-310
0.550 kg
ASTM F2413:2018
EN ISO 20345:2022+A1:2024



TLS#####
Safety Jogger#####TLS#####
#####TLS#####
#####TLS#####
#####TLS#####




#####



#####ESD#
ESD#####

##100 KiloOhm##100 MegaOhm
#####



#####



#####



(SR)
#####SRA+SRB=SRC#####
#####SR#####
#####



BLK



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

#####:
##, #####, ##, #####, #####

#####:
#####, #####, ####

#####:
#####

####		####	#	EN ISO 20345
##	#####, ####			
	#####	mg/cm²/h	21.09	# 0.8
	#####	mg/cm²	169	# 15
##	#####			
	#####	mg/cm²/h	49.8	# 2
	#####	mg/cm²	398.8	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/###			
	#####	mm³	128	# 150
	##### - #####NaLS - #####	####	0.48	# 0.31
	##### - #####NaLS - #####	####	0.43	# 0.36
	SR ### - ##### - #####	####	0.41	# 0.19
	SR##### - ##### - #####	####	0.34	# 0.22
	#####	####	14.6	0.1 - 1000
	ESD#	####	11.6	0.1 - 100
	#####	J	35	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	18.5	# 14
	#####15kN#	mm	23.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com