

##:
####, ###, ##, ##, ###

##:
##, ## ##### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##			
	##: ### ##	mg/cm ² /h	21.09	# 0.8
	##: ### ##	mg/cm ²	169	# 15
## ##	### ##			
	##: ### ##	mg/cm ² /h	49.8	# 2
	##: ### ##	mg/cm ²	398.8	# 20
##	SJ ### # ###			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	### #####(## ##)	mm ³	128	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.48	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.43	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.41	# 0.19
	SR ### ## - ### + ##### - ## ## ##	##	0.34	# 0.22
	### ## #	###	14.6	0.1 - 1000
	ESD #	###	11.6	0.1 - 100
	##### ## ##	J	35	# 20
Top	##			
	##### ## ##(## # ## 100J)	mm	N/A	N/A
	##### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	##### ## ##(## # ## 200J)	mm	18.5	# 14
	##### ## ##(## # ## ## 15kN)	mm	23.0	# 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## # #####.



**HEAD-TO-TOE
PROTECTION**

Proudly ranked in the top 1% by EcoVadis for sustainability.

