

**SAFETY
JOGGER**
INDUSTRIAL



#####

ASAMA S3S MID TLS


ASAMAS3MTL

TLS

Phylon

ASAMAS3MTL Safety Jogger ##### TLS,
#####, #####
ESD

#####	#####, #####
#####	#####
#####	##### SJ Memory Foam
#####	#####
#####	##### ####
#####	##### ####
#####	S3S / ####, ESD, ####, #.##, ####, ##
#####	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
#####	JPN 21.5-31 / KOR 230-310
#####	0.550 kg
#####	ASTM F2413:2018
#####	EN ISO 20345:2022+A1:2024



TLS #####
TLS ##### Safety Jogger #####

TLS #####

#####



(ESD)
ESD #####


100 ##### 100 #####
#####




#####



BLK



#####



#####



(SR)
SRA+SRB=SRC SR

#####

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

#####:

#####, #####, #####, #####, #####

#####:

#####, #####, #####

#####:

#####

#####		#####	#####	EN ISO 20345
#####	#####, #####			
	#####: #####	##./##./##	21.09	# 0.8
	#####: #####	##./##	169	# 15
#####	#####			
	#####: #####	##./##./##	49.8	# 2
	#####: #####	##./##	398.8	# 20
#####	##### SJ Memory Foam			
	#####: ##### (####/#) (#)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/#####			
	##### (#####)	##	128	# 150
	- ##### + NaLS - #####	#####	0.48	# 0.31
	- ##### + NaLS - #####	#####	0.43	# 0.36
	SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.41	# 0.19
	##### SR - ##### + ##### - #####	#####	0.34	# 0.22
	#####	#####	14.6	0.1 - 1000
	## ESD	#####	11.6	0.1 - 100
	#####	##	35	# 20
#####	#####			
	(##### 100J)	##	N/A	N/A
	(##### 10kN)	##	N/A	N/A
	(##### 200J)	##	18.5	# 14
	(##### 15kN)	##	23.0	# 14

####:

Safety Jogger

