



**SAFETY  
JOGGER**  
PROFESSIONAL



**Light**

# ATUM OB

ATUMOB

**Running-inspired occupational trainer with an ultra breathable mesh upper**

The ATUM OB from Safety Jogger is a stylish, lightweight shoe with a breathable upper and removable footbed. Perfect for assembly, logistics, medical and catering industries.

Upper	Knitted Textile
Lining	Textile
Footbed	SJ foam footbed
Outsole	TPR/EVA
Category	OB / SR, E
Size range	EU 35-48
Sample weight	0.338 kg
Norms	EN ISO 20347:2022+A1:2024




BLK




LGR




**Breathable upper**  
Increased moisture and temperature management for extended wearer comfort.



**Slip resistance (SR)**  
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



**Removable insole**  
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



**SJ Foam**  
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.




**Solutions for every workplace**

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

**ENGINEERED  
IN EUROPE**

www.safetyjogger.com

**Industries:**

Catering, Assembly, Logistics, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Knitted Textile</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	63.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	509.2	≥ 15
<b>Lining</b>	<b>Textile</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	11.7	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	94.2	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
<b>Outsole</b>	<b>TPR/EVA</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	104.4	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.39	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.40	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.20	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.23	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	43	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.