



#

BASALT S7S

#####

BASALT ##### SR #####
#####


##	###, ###
##	###
##	SJ #####
##	#####
##	###PU/###
##	#####
##	S7S / SR, SC, LG, ESD, HI, CI, FO, HRO
####	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
####	0.820 kg
##	ASTM F2413:2018 EN ISO 20345:2022



S3
S3#####
#####



####(ESD)
ESD#####
#####10###35 #
#####




#####



##WR#
#####



SRC##
SRC##
#SRA#SRB#####
#####



#####



BLK

##:
##, ##, ##, ##, ##, ##, ##, ##

##:
####, ####, ####, ####, ####

####:
#####

##		####	##	EN ISO 20345
##	###, ###			
	#####	##/####/##	1.1	#### 0.8
	#####	##/####	23	#### 15
##	###			
	#####	##/####/##	2.4	#### 2
	#####	##/####	23	#### 20
##	SJ #####			
	#####/#####	##	25600/12800	25600/12800
##	###PU/####			
	#####	## ³	91	#### 150
	#### - ## + NaLS - ####	##	0.41	#### 0.31
	#### - ## + NaLS - #####	##	0.37	#### 0.36
	SR ## - ## + ## - ####	##	0.28	#### 0.19
	SR ## - ## + ## - #####	##	0.25	#### 0.22
	####	##	54	0.1 - 1000
	ESD#	##	58	0.1 - 100
	####	J	28	#### 20
	#####			
##	#####100J#	##	N/A	N/A
	#####10kN#	##	N/A	N/A
	#####200J#	##	16.5	#### 14
	#####15kN#	##	20.0	#### 14

####:
#####Safety Jogger#####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com