



Heavy

## BESTBOOT2 S3


### Robust leather safety boot

The Safety Jogger BESTBOOT2 ensures top-notch safety with a robust steel toecap, antistatic properties, and a puncture-resistant midsole. Comfort and utility are guaranteed with posture pain relief, cool feet, and a self-cleaning outsole.

Upper	Barton Action Leather
Lining	Cambrella
Footbed	SJ foam footbed
Midsole	Steel
Toecap	Steel
Category	S3 / SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.809 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK




#### Oil & fuel resistant

The outsole is resistant against oil and fuel.



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm




#### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



#### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



#### Self-cleaning outsole

Self-cleaning outsoles are designed to reduce clogging of the profile.

**Industries:**

Chemical, Construction, Mining, Oil &amp; Gas, Industry

**Environments:**

Muddy environment, Uneven surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	18.3	≥ 15
<b>Lining</b>	<b>Cambrella</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	33.5	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	269	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	17.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.