



**SAFETY
JOGGER**
INDUSTRIAL



###

BESTBOOT2 **S3**

#####

Safety Jogger BESTBOOT2#####

#####

#####

#####

SJ#####

#####

##PU/##PU


#####

S3 / SRC

EU 36-47 / UK 3.5-12.0 / US 4.0-13.0
JPN 22.5-31 / KOR 235-310

0.809 kg

ASTM F2413:2024
EN ISO 20345:2011



#####




S3
S3#####

#####




#####100 KiloOhm##1 GigaOhm
#####



#####



##



#####

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

####:
####, ##, ##, #####, ####

#####:
####, #####

#####:
#####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm²/h	1.9	# 0.8
	#####	mg/cm²	18.3	# 15
##	####			
	#####	mg/cm²/h	33.5	# 2
	#####	mg/cm²	269	# 20
####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	###PU/###PU			
	#####	mm³	24.3	# 150
	##### SRA####	#####	0.34	# 0.28
	##### SRA####	#####	0.33	# 0.32
	##### SRB####	#####	0.16	# 0.13
	##### SRB####	#####	0.19	# 0.18
	#####	#####	150.9	0.1 - 1000
	ESD#	#####	N/A	0.1 - 100
	#####	J	27	# 20
#####	####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	16.0	# 14
	#####15kN#	mm	17.0	# 14

#####.
#####Safety Jogger #####



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com