



Medium

BESTBOY2 S3

Leather Non-Slip Safety Boots

BESTBOY2 midcut safety shoes feature a steel toecap and midsole for impact protection, and breathable leather to keep feet cool and fresh all day.

Upper	Barton Action Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, SC, CI, FO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.660 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



210



DGVU BGR 191

These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

Industries:

Automotive, Chemical, Cleaning, Construction, Mining, Oil & Gas, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Barton Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.2	# 0.8
	Upper: water vapor coefficient	mg/cm²	25.0	# 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm²/h	49.8	# 2
	Lining: water vapor coefficient	mg/cm²	398.8	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	35.6	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.43	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.24	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.26	# 0.22
	Antistatic value	MegaOhm	55.1	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	23	# 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.5	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com