



BESTBOY2 S3

Bestboy

Safety Jogger BESTBOY2 #####
SR, #####

#####

#####	#####
#####	#####
#####	SJ #####
#####	#####
#####	PU/PU
#####	#####
#####	S3 / ####.####, ##, ##.##, #####
#####	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0
#####	JPN 22.5-31 / KOR 235-310
#####	0.660 kg
#####	EN ISO 20345:2022+A1:2024
#####	ASTM F2413:2024



DGUV BGR 191

BGR 191



210



S3

S3 #####

#####



SRC

SRC ##### SRA ##### SRB
#####



#####

#####



#####

#####



#####

#####

#####:

#####, #####, #####, #####, #####, #####, #####, #####, #####

#####:

#####:

#####

#####	#####	#####	#####	EN ISO 20345
#####	#####	##./##./##	2.2	# 0.8
#####	#####	##./##	25.0	# 15
####	#####			
####	#####	##./##./##	49.8	# 2
####	#####	##./##	398.8	# 20
#####	SJ #####			
#####	#####: ##### (####/#) (#)	###	25600/12800	25600/12800
#####	PU/PU			
#####	##### (#####)	##	35.6	# 150
#####	- ##### + NaLS - #####	#####	0.43	# 0.31
#####	- ##### + NaLS - #####	#####	0.45	# 0.36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.24	# 0.19	
##### SR - ##### + ##### - #####	#####	0.26	# 0.22	
#####	#####	55.1	0.1 - 1000	
### ESD	#####	N/A	0.1 - 100	
#####	##	23	# 20	
####	####			
#####	(##### 100J)	##	N/A	N/A
#####	(##### 10kN)	##	N/A	N/A
#####	(##### 200J)	##	18.5	# 14
#####	(##### 15kN)	##	20.5	# 14

####:

Safety Jogger

