



Medium

## BESTBOY252 S3

All-time favorite, mid-cut safety shoe

Safety Jogger's BESTBOY252 is a mid-cut safety shoe that offers antistatic properties, heel energy absorption, and a breathable upper. Perfect for a wide range of industries, it provides all-day comfort and unrivaled protection.

Upper	Barton Action Leather
Lining	Teddy
Footbed	Teddy
Midsole	Steel
Outsole	PU/Rubber
Toecap	Steel
Category	S3 / SR, CI, FO, HRO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.720 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022




BLK



### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

**Industries:**

Automotive, Chemical, Construction, Logistics, Mining, Oil &amp; Gas, Industry

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	25.0	≥ 15
<b>Lining</b>	<b>Teddy</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	33.5	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	269	≥ 20
<b>Footbed</b>	<b>Teddy</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	135	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.40	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.20	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	621	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	31	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.