

# SAFETY JOGGER


PROFESSIONAL

CLOGS

## BESTCLOG OB


Fashionable ultra-light clog for all day comfort

|                 |  |
|-----------------|--|
| Upper           | Expanded EVA   |
| Outsole         | EVA/Rubber   |
| Toecap          |  |
| Midsole         |  |
| Lining          |  |
| Footbed         | SJ foam footbed  |
| Safety category | EN ISO 20347 - OB / SRC                                |
| Sample weight   | 250 gr.  |
| Size range      | EU 36-46 / UK 3.5-11.0 /<br>US 4.0-12.0 / CM 23.5-30.0 |



### WASHABLE 30°C

These shoes can be washed in a washing machine at 30°C.



### CHEMICALLY & UV STERILIZEABLE

This shoe is chemically and UV sterilizeable.



## CLOGS

### BESTCLOG OB

**Industries:**

Catering, Cleaning, Food & beverages, Medical

**Environments:**

Dry environment, Extreme slippery surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result      | EN ISO 20347 |
|----------------|--|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Expanded EVA</b>  |                       |             |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | NA          | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | NA          | ≥ 15         |
| <b>Lining</b>  | <b>N/A</b>   |                       |             |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | NA          | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | NA          | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>   |                       |             |              |
|                | Footbed: abrasion resistance                                     | cycles                | 25600/12800 | ≥ 400        |
| <b>Outsole</b> | <b>EVA/Rubber</b>  |                       |             |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 96          | ≤ 150        |
|                | Outsole slip resistance SRA: heel                                | friction              | 0.35        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat                                | friction              | 0.35        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel                                | friction              | 0.21        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat                                | friction              | 0.22        | ≥ 0.18       |
|                | Antistatic value   | MegaOhm               | NA          | 0.1 - 1000   |
|                | ESD value  | MegaOhm               | NA          | 0.1 - 100    |
|                | Heel energy absorption   | J                     | NA          | ≥ 20         |
| <b>Toecap</b>  |  |                       |             |              |
|                | Impact resistance toecap (clearance after impact 100J)           | mm                    | NA          | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 10kN) | mm                    | NA          | ≥ 14         |
|                | Impact resistance toecap (clearance after impact 200J)           | mm                    | NA          | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 15kN) | mm                    | NA          | ≥ 14         |

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*

Sample size: 41