



Medium

BESTFIT S1 P

Safety boot with heel tab and elasticated sides

The Safety Jogger BESTFIT safety shoe combines advanced features like SRC slip resistance, antistatic properties, and puncture-resistant steel midsole. It offers unmatched comfort with its breathable leather upper and removable footbed, ideal for demanding industries.

Upper	Nappa Action Leather
Lining	Cambrella
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SRC
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.678 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



DBN




BLK



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Mining, Oil & Gas, Industry

Environments:

Dry environment, Muddy environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.7	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	18.5	≥ 15
Lining	Cambrella			
	Lining: permeability to water vapor	mg/cm ² /h	33.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	269	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	24.3	≤ 150
	Outsole slip resistance SRA: heel	friction	0.34	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	223	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	33	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.