



BESTFIT S1 P

#####

Safety Jogger BESTFIT#####SR#####

SJ#####

PU/PU

S1 P / SRC
EU 36-48 / UK 3.5-13.0 / US 4.0-13.5
JPN 22.5-31.5 / KOR 235-315
0.678 kg
ASTM F2413:2018
EN ISO 20345:2011



#####



#####



#####



#####



100 KiloOhm##1 GigaOhm
#####



S3
S3#####
#####



DBN



BLK

#####:

#####, #####, ####, #####, ##, #####, #####, ##, #####, ####

#####:

#####, #####, #####

#####:

#####

	####	####	##	EN ISO 20345
####	#####			
	#####	mg/cm ² /h	1.7	# 0.8
	#####	mg/cm ²	18.5	# 15
##	####			
	#####	mg/cm ² /h	33.5	# 2
	#####	mg/cm ²	269	# 20
#####	SJ#####			
	#####	####	25600/12800	25600/12800
#####	PU/PU			
	#####	mm ³	24.3	# 150
	##### SRA####	####	0.34	# 0.28
	##### SRA####	####	0.33	# 0.32
	##### SRB####	####	0.16	# 0.13
	##### SRB####	####	0.19	# 0.18
	####	####	223	0.1 - 100
	ESD#	####	N/A	0.1 - 100
	#####	J	33	# 20
#####	####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	17.5	# 14
	#####15kN#	mm	21.0	# 14

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com