



## BESTFIT S1 P

#####
 Safety Jogger BESTFIT #####
 SR #####
 SJ #####
 PU/PU #####
 #####
 S1 P / ####.####.##
 EU 36-48 / UK 3.5-13.0 / US 4.0-13.5  
 JPN 22.5-31.5 / KOR 235-315 #####
 0.678 kg #####
 ASTM F2413:2018 #####
 EN ISO 20345:2011 #####

#####	#####
#####	#####
#####	SJ #####
#####	#####
#####	PU/PU
#####	####
#####	S1 P / ####.####.##
#####	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
#####	0.678 kg
#####	ASTM F2413:2018
#####	EN ISO 20345:2011



#####
 #####
 #####
 100 #####
 1 #####

#####
 #####
 S3 #####
 #####
 #####

#####: #####, #####, #####

#####:

#####		#####	#####	EN ISO 20345
#####	#####			
#####:	#####	##./##./##	1.7	# 0.8
#####:	#####	##./##	18.5	# 15
#####	#####			
#####:	#####	##./##./##	33.5	# 2
#####:	#####	##./##	269	# 20
#####	SJ #####			
#####:	##### (####/#) (###)	###	25600/12800	25600/12800
##### PU/PU				
#####	(##### (#####))	##	24.3	# 150
#####	SRA: #####	#####	0.34	# 0.28
#####	SRA: ###	#####	0.33	# 0.32
#####	SRB: #####	#####	0.16	# 0.13
#####	SRB: ###	#####	0.19	# 0.18
#####		#####	223	0.1 - 1000
### ESD		#####	N/A	0.1 - 100
#####		##	33	# 20
#####	#####			
#####	(##### 100J)	##	N/A	N/A
#####	(##### 10kN)	##	N/A	N/A
#####	(##### 200J)	##	17.5	# 14
#####	(##### 15kN)	##	21.0	# 14

####:

##### Safety Jogger #####

