



##

### BESTFIT S1 P

#####  
 Safety Jogger BESTFIT #### SRC #####  
 #####

##	#####
##	#####
##	SJ #####
##	-
##	###PU/###PU
##	-
##	S1 P / SRC
####	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
####	0.678 kg
##	ASTM F2413:2018 EN ISO 20345:2011



BLK



DBN



#####  
 #####



####  
 #####



####  
 #####



####  
 #####



###  
 #####  
 #10###1#####



S3  
 S3#####  
 #####

##:  
##, ##, ##, ##, ##, #####, ##, ##, ##, ##

##:  
####, ####, #####

####:  
#####

##	####	##	EN ISO 20345
##	#####		
	#####	##/####/#	1.7 #### 0.8
	#####	##/####	18.5 #### 15
##	#####		
	#####	##/####/#	33.5 #### 2
	#####	##/####	269 #### 20
##	<b>SJ #####</b>		
	#####/#####	##	25600/12800 25600/12800
##	<b>##PU/##PU</b>		
	#####	## <sup>3</sup>	24.3 #### 150
	#####SRA###	##	0.34 #### 0.28
	#####SRA###	##	0.33 #### 0.32
	#####SRB###	##	0.16 #### 0.13
	#####SRB###	##	0.19 #### 0.18
	####	##	223 0.1 - 1000
	ESD#	##	N/A 0.1 - 100
	####	J	33 #### 20
##	-		
	#####100J#	##	N/A N/A
	#####10kN#	##	N/A N/A
	#####200J#	##	17.5 #### 14
	#####15kN#	##	21.0 #### 14

####:  
#####Safety Jogger#####



HEAD-TO-TOE PROTECTION

