SAFETY JOGGER
INDUSTRIAL

Medium

BESTFIT3 S3

BESTFIT3S3

Chelsea-style Safety Boot

Breathable S3 safety shoe with steel toe, ladder grip, memory foam comfort, and a PU/PU outsole for superior cushioning and impact absorption.

Upper	Micro Nappa Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, SC, LG, FO, CI
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.650 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024

BLK

CO_2 12.01 kg

Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

Oil & fuel resistant
The outsole is resistant against oil and fuel.

Ladder Grip (LG)
Especially defined contour in the shank area of a safety shoe to provide additional safety while standing on ladders.

Scuff Cap (SC)
Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.

Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.

Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.

SAFETY JOGGER WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:
Automotive, Chemical, Cleaning, Construction, Food & beverages, Logistics, Mining, Oil & Gas, Industry

Environments:
Dry environment, Uneven surfaces, Muddy environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Micro Nappa Leather**			
	Upper: permeability to water vapor	≥ 0.8	2.8	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	30.6	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	86.31	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	691	mg/cm^2
Footbed	**SJ Recycled Memory Foam Footbed (90% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	137	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.4	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.41	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.29	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.3	friction
	Antistatic value	0.1 - 1000	33.6	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	30	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	15	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	20.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	9.73	kg
	Packing	0.13	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		12.01 kg CO2/pair	

	Description	Result
Recycled content		
	Product	7%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.