

Medium

BESTRUN3 S3

BESTRUN3S3

Steel Toe Low-cut Safety Shoes

The BESTRUN3 S3 delivers ultimate steel toe and midsole protection, a breathable leather upper, cold insulation, a scuff cap, and ladder grip.

Upper	Leather
Lining	Mesh
Footbed	SJ Memory foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, SC, LG, FO, CI
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.625 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Cold insulated (CI)

Cold insulated (CI)
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Ladder Grip (LG)

Especially defined contour in the shank area of a safety shoe to provide additional safety while standing on ladders.




Memory foam

Removable memory foam
The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



Scuff Cap (SC)

Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Oil & fuel resistant

The outsole is resistant against oil and fuel.

Industries:

Construction, Automotive, Chemical, Cleaning, Logistics, Oil & Gas, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment, Muddy environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Leather			
	Upper: permeability to water vapor	mg/cm² /h	2.21	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	21	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm² /h	21.45	≥ 2
	Lining: water vapor coefficient	mg/cm²	172	≥ 20
Footbed	SJ Memory foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	137	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.4	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.41	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	3.0	≥ 0.22
	Antistatic value	MegaOhm	33.6	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.