

Medium

BESTRUN METALFREE S3 S3S

BESTRUNMF


Metal-Free Safety Shoe s3

Enjoy lightweight comfort and strong protection with BESTRUN METALFREE shoes. Stay safe with a composite toe, slip resistance and all day support.

Upper	Barton Action Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Composite
Category	S3S / SR, SC, LG, ESD, CI, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.655 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022+A1:2024




BLK



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity



Self-cleaning outsole

Self-cleaning outsoles are designed to reduce clogging of the profile.



Non-marking outsole

Non-marking outsoles do not leave color marks on the ground.

Industries:

Assembly, Automotive, Industry, Logistics

Environments:

Uneven surfaces, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Barton Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.2	# 0.8
	Upper: water vapor coefficient	mg/cm²	25	# 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm²/h	49.8	# 2
	Lining: water vapor coefficient	mg/cm²	398.8	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	56.4	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.41	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.27	# 0.22
	Antistatic value	MegaOhm	32.6	0.1 - 1000
	ESD value	MegaOhm	29	0.1 - 100
	Heel energy absorption	J	26	# 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.0	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22.5	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com