



Light

## BESTSUN S1P

BESTSUNS1P

Leather Sandal Velcro Closure

Work with confidence in Safety Jogger BESTSUN S1P sandals. Lightweight, breathable leather with toe protection, slip resistance and customizable comfort.

Upper	Barton Action Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Norms	ASTM F2413:2018 EN ISO 20345:2022



BLK



**Breathable leather upper**  
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



**Removable insole**  
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.




**Non-marking outsole**  
Non-marking outsoles do not leave color marks on the ground.



**S1P**  
You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



**SJ Foam**  
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



**Antistatic**  
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

**SAFETY  
JOGGER**  
WORKS

**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Assembly, Automotive, Industry, Logistics

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	2.2	# 0.8
	Upper: water vapor coefficient	mg/cm²	25	# 15
Lining	<b>Recycled Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	49.8	# 2
	Lining: water vapor coefficient	mg/cm²	398.8	# 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	56.4	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.41	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.29	# 0.22
	Antistatic value	MegaOhm	120.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	29	# 20
Toecap	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com