



#####

## BESTGIRL S3 LOW

BSTGRLS3LO

Bestgirl ##### 2 #####

##### S3 #####  
##### ESD #####  
##### BESTGIRL #####  
#####  
#####

#####	#####
#####	#####
#####	SJ #####
#####	#####
#####	PU/PU
#####	#####
#####	S3 / ####, ####, ESD, ##, ####
#####	EU 35-43
#####	0.498 kg
#####	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



##### (LG)



#####  
#####  
#####  
#####



SJ #####  
#####  
#####  
#####  
#####



Proudly ranked in the top 1% by EcoVadis for sustainability.

#####:

#####, #####, #####, #####, #####, #####, #####, #####, #####

#####:

#####:

#####

#####	#####	#####	#####	EN ISO 20345
#####	#####	##./##./##	2.3	# 0.8
	#####: #####	##./##	29.4	# 15
#####	#####	##./##./##	86.31	# 2
	#####: #####	##./##	691	# 20
#####	SJ #####	###	Dry 25600 cycles/Wet 12800 cycles	25600/12800
	#####: ##### (####/####) (###)			

##### PU/PU

#####	#####	##### (#####)	##	29.9	# 150
##### - ##### + NaLS - #####	#####	#####	##	0.42	# .31
##### - ##### + NaLS - #####	#####	#####	##	0.46	# .36
SR Slip Resistance - Ceramic + Glycerin - #####	#####	#####	##	0.21	# .19
##### SR - ##### + ##### - #####	#####	#####	##	0.24	# .22
#####	#####	#####	##	13.2	0.1 - 1000
### ESD	#####	#####	##	13	0.1 - 100
#####	##	##	##	31	# 20
#####	#####	##### (##### 100J)	##	N/A	N/A
##### (##### 10kN)	##	##	##	N/A	N/A
##### (##### 200J)	##	##	##	15.0	# 14
##### (##### 15kN)	##	##	##	20.0	# 14

# # # #

||||| Safety Jogger |||||

