

BESTLADY S3 MID

BESTLADY women's safety shoes combine breathable leather, steel safety, ESD protection and strong slip resistance for dependable S3-rated performance.

A side-profile photograph of a black leather hiking boot. The boot features white contrast stitching along the seams and eyelets. It has a thick, light-colored midsole and a dark, treaded outsole. The laces are black with white tips. A small, dark logo is visible on the side of the boot. The background is plain white.

Industries:

Assembly, Automotive, Industry, Logistics, Oil & Gas, Food & beverages

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Full Grain Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.3	# 0.8
	Upper: water vapor coefficient	mg/cm²	29.4	# 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm²/h	86.31	# 2
	Lining: water vapor coefficient	mg/cm²	691	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	29.9	# 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.42	# 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.46	# 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.21	# 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.24	# 0.22
	Antistatic value	MegaOhm	13.2	0.1 - 1000
	ESD value	MegaOhm	13	0.1 - 100
	Heel energy absorption	J	31	# 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	# 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.0	# 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com