

#

CADOR S1P MID

CADORMID

ESD

CADOR S1P MID #### ## ### ###, S1P ## ##, SR ###
ESD ## ##### ## ## ### #####, ## #### ##### ####.

## ##	##
## ##	3D ##
##	SJ # ##
##	##
## #	PU / PU
Top	##
####	S1 P / SR, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.609 kg
###	ASTM F2413:2018 EN ISO 20345:2022



GRY




S1P

##, ## ##, ### # ## ##
#####? ##### S1P #####.



##

```
ESD# ## ### ##### # ## ### #####
### ##### ##### ## ## ### #####. ##
### 100##### 100### #####.
```



##

#####.



#

##.



###

```
## ## ## ##### ##### ## ## ## ##
## ## ## ## ## ## ## ## ##
#####.
```



###

#####.

##:
####, ###, ## # ##, ##, ##

##:
##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ###	mg/cm²/h	3.9	# 0.8
	##: ### ##	mg/cm²	41	# 15
## ##	3D ##			
	##: ### ###	mg/cm²/h	61.1	# 2
	##: ### ##	mg/cm²	490	# 20
##	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
## #	PU / PU			
	### ####(## ##)	mm³	59	# 150
	### ## ## SRA: ###	##	0.30	# 0.28
	## SRA# ### ##: ##	##	0.39	# 0.32
	### ## ## SRB: ###	##	0.15	# 0.13
	## ## SRB# ### ##: ##	##	0.24	# 0.18
	### ## #	###	8.1	0.1 - 1000
	ESD #	###	73	0.1 - 100
	#### ## ##	J	24	# 20
	##			
Top	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## 200J)	mm	15.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	19.0	# 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com