

# SAFETY JOGGER

## INDUSTRIAL



#

### CADOR S1P MID

CADORMID

#####

Safety Jogger##### CADOR S1P MID #####S1P #####SR #  
## ESD #####

##	###
##	3D ###
##	SJ #####
##	-
##	###PU/###PU
##	-
##	S1 P / SR, ESD, FO
####	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
####	0.609 kg
##	ASTM F2413:2018 EN ISO 20345:2022



GRY



**S1P**  
#####  
#####S1P  
###

**###(ESD)**  
ESD#####  
#####10###35 #  
#####

**Airblaze##**  
#####  
###

#####  
#####  
##

#####  
#####

#####  
#####

##:  
##, ##, #####, ##, ##

##:  
####

####:  
#####

##	####	##	EN ISO 20345	
##	##### #####	##/####/# ##/####	3.9 41	#### 0.8 #### 15
##	3D #### ##### #####	##/####/# ##/####	61.1 490	#### 2 #### 20
##	SJ ##### #####/#####	##	25600/12800	25600/12800
##	###PU/###PU ##### #####SRA### #####SRA### #####SRB### #####SRB### #### ESD# ####	## <sup>3</sup> ## ## ## ## ## ## ## J	59 0.30 0.39 0.15 0.24 8.1 73 24	#### 150 #### 0.28 #### 0.32 #### 0.13 #### 0.18 0.1 - 1000 0.1 - 100 #### 20
##	- #####100J# #####10kN# #####200J# #####15kN#	## ## ## ##	N/A N/A 15.0 19.0	N/A N/A #### 14 #### 14

####:

#####Safety Jogger#####



HEAD-TO-TOE  
PROTECTION

