



#####

CADOR S1P SANDAL

CADORSNDL

#####ESD#####

#####S1P#####ESD#####

#####Airblaze#####

3D-###
SJ#####

PU/PU

S1 P / SR, ESD, #####
EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315
0.605 kg
ASTM F2413:2018
EN ISO 20345:2022



#####



SRC#####
#####1##
##SRC##SRA#SRB#####

####



#####



##



####



#####ESD#
ESD#####

##100 KiloOhm##100 MegaOhm
#####



GRY

#####:

##, #####, ##, #####

#####:

##

#####:

#####

| | #### | #### | # | EN ISO 20345 |
|-------|----------------|-----------------------|-------------|--------------|
| #### | #### | | | |
| | ##### | mg/cm ² /h | 3.9 | # 0.8 |
| | ##### | mg/cm ² | 41 | # 15 |
| ## | 3D-### | | | |
| | ##### | mg/cm ² /h | 61.1 | # 2 |
| | ##### | mg/cm ² | 490 | # 20 |
| ##### | SJ##### | | | |
| | ##### | #### | 25600/12800 | 25600/12800 |
| ##### | PU/PU | | | |
| | ##### | mm ³ | 59 | # 150 |
| | ##### SRA### | #### | 0.30 | # 0.28 |
| | ##### SRA### | #### | 0.39 | # 0.32 |
| | ##### SRB### | #### | 0.15 | # 0.13 |
| | ##### SRB### | #### | 0.24 | # 0.18 |
| | #### | #### | 8.1 | 0.1 - 1000 |
| | ESD# | #### | 73 | 0.1 - 100 |
| | ##### | J | 24 | # 20 |
| ##### | #### | | | |
| | #####100J# | mm | N/A | N/A |
| | #####10kN##### | mm | N/A | N/A |
| | #####200J# | mm | 15.0 | # 14 |
| | #####15kN# | mm | 19.0 | # 14 |

#####:

#####Safety Jogger #####



**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com