



CHAMP Q2 LOW

CHAMPO?

CHAPTER 2

#####	#####
#####	#####
#####	SJ #####
#####	#####/#####
#####	O2 / ESD, ###.###.##, #####
#####	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
#####	JPN 21.5-31 / KOR 230-310
#####	0.306 kg
#####	ASTM F2892:2018
#####	EN ISO 20347:2012




BLK



WHT





(ESD)



#####
 #####
#####
 #####
#####
 #####



#####



#####
 #####

#####

#####



HEAD-TO-TOE PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

#####:

#####:

#####, #####, #####

#####:#####:

#####

#####		#####	#####	EN ISO 20347
#####	#####	##./##./##	2.4	# 0.8
#####	#####	##./##	21.3	# 15
#####	#####	##./##./##	17.4	# 2
#####	#####	##./##	140	# 20
#####	SJ #####			
#####	#####: ##### (###/###) (###)	###	25600/12800	25600/12800
#####	#####			
#####	##### (##### (#####))	##	142.8	# 150
#####	SRA: #####	#####	0.32	# 0.28
#####	SRA: ###	#####	0.35	# 0.32
#####	SRB: #####	#####	0.21	# 0.13
#####	SRB: ###	#####	0.21	# 0.18
#####		#####	N/A	0.1 - 1000
### ESD		#####	37.9	0.1 - 100
#####		##	35	# 20

#####:

Safety Jogger