



##


## CHAMP O2 LOW

CHAMPO2


#####

##Safety Jogger CHAMP O2 LOW #####  
##SR ##ESD #####

## Lorica  
## #####  
## SJ #####  
## #####  
## O2 / ESD, SRC, FO  
#### EU 35-47 / UK 3.0-12.0 / US 3.0-13.0  
JPN 21.5-31 / KOR 230-310  
#### 0.306 kg  
## ASTM F2892:2018  
EN ISO 20347:2012




####(ESD)  
ESD#####  
#####10###35 #  
#####



###  
#####




#####



#####



####  
#####



####  
#####



BLK



WHT



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

##:  
##, ##, #####, ##

##:  
####, ####, #####

####:  
#####

##	##	####	##	EN ISO 20347
##	<b>Lorica</b>			
	#####	##/##/##/##	2.4	#### 0.8
	#####	##/##/##	21.3	#### 15
##	####			
	#####	##/##/##/##	17.4	#### 2
	#####	##/##/##	140	#### 20
##	<b>SJ #####</b>			
	#####/#####	##	25600/12800	25600/12800
##	##/##/##			
	#####	## <sup>3</sup>	142.8	#### 150
	####SRA##	##	0.32	#### 0.28
	####SRA##	##	0.35	#### 0.32
	####SRB##	##	0.21	#### 0.13
	####SRB##	##	0.21	#### 0.18
	####	##	N/A	0.1 - 100
	ESD#	##	37.9	0.1 - 100
	####	J	35	#### 20

####:

#####, #####Safety Jogger#####



**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)