



SAFETY JOGGER

PROFESSIONAL



Medium

CLARK 01

Low, leather sneaker for him

The CLARK shoes are stylish, leather sneakers with advanced ESD. Perfect for various industries, they offer customizable comfort, excellent grip, and protection against static sparks.


Upper	Action Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Outsole	Rubber (NBR)
Category	O1 / ESD, SRC
Size range	EU 39-47 / UK 6.0-12.0 / US 6.5-13.0 JPN 25-31 / KOR 255-310
Sample weight	0.360 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



NAV



Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY
JOGGER

WORKS

HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.5	# 0.8
	Upper: water vapor coefficient	mg/cm²	28.9	# 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm²/h	59.1	# 2
	Lining: water vapor coefficient	mg/cm²	473	# 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	65	# 150
	Outsole slip resistance SRA: heel	friction	0.4	# 0.28
	Outsole slip resistance SRA: flat	friction	0.4	# 0.32
	Outsole slip resistance SRB: heel	friction	0.17	# 0.13
	Outsole slip resistance SRB: flat	friction	0.21	# 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	21	0.1 - 100
	Heel energy absorption	J	20	# 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com