



## CONSTRUCTO 3PACK 3243X

CONSTRU3P

### Seamless Cotton Safety Gloves

CONSTRUCTO safety gloves offer a flexible cotton polyester liner with strong latex grip, high abrasion resistance and great dexterity.

Performance level	3243X
Liner	10 Gauge/Polyester/Cotton/Rubber(NBR)
Coating	Latex Crinkle Coated
Category	SIF-Silicone Free
Size range	EU 6-12
Sample weight	0.047 kg
Norms	ANSI/ISEA 105:2016 EN ISO 21420:2020 EN 388:2016



EN ISO 21420

EN 388:2016



### Industries:

Chemical, Cleaning, Construction, Industry, Mining, Oil & Gas

### Extraordinary grip

You'll have a firm hold on objects whether they are dry, wet, or oily, thanks to the exceptional grip these gloves provide.



025

### Performance level 3243X

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (factor)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (newton)	2	5	10	15	22	30

- Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- Tear resistance: based on the amount of force required to tear the sample.
- Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.