SAFETY JOGGER
INDUSTRIAL

中等

DAKAR S3 LEATHER

DAKARS3LEA

全皮系鞋带靴

Safety Jogger's DAKAR S3 LEATHER is a high-performance safety boot with SR slip-resistant soles, antistatic properties, and oil & fuel resistance. It features a breathable leather upper, removable footbed and heel energy absorption for comfort and durability.

鞋面	头层疯马皮
内里	透气网布
鞋垫	SJ 抗菌防臭海波丽鞋垫
中底	-
大底	聚氨酯PU/聚氨酯PU
鞋头	-
等级	S3 / SRC
大小范围	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
样品重量	0.764 kg
标准	ASTM F2413:2018 EN ISO 20345:2011

BLK

BRN

防静电
防静电鞋可以防止静电电荷的积聚，确保其有效放电。 体积电阻在10万欧姆至1千兆欧姆之间。

透气皮革鞋面
天然皮革彰显卓越舒适性，经久耐用，用途广泛。

后跟吸能
后跟吸能减缓跳跃或奔跑对身体的冲击。

无痕外底
无痕外底不会在地面上留下色痕。

耐燃油性
外底耐燃油性

S3
S3安全鞋适合在高湿度和存在油类或碳氢化合物的环境中工作。这类鞋子还可以防止鞋底穿孔风险及脚部挤压。

工业:
装修，化学，建筑，工业，物流

环境:
干燥环境，潮湿环境，泥地环境

维护指南:
建议定期清洁鞋类，并使用适当的产品保养，旨在延长鞋类寿命。 不得将鞋子摆放至暖气片上烘干，不得在热源附近烘干。

	描述	测量单位	结果	EN ISO 20345
鞋面	**头层疯马皮**			
	帮面：水蒸气渗透性	毫克/平方厘米/小时	2.1	大于等于 0.8
	帮面：水蒸气系数	毫克/平方厘米	18.3	大于等于 15
内里	**透气网布**			
	衬里：水蒸气渗透性。	毫克/平方厘米/小时	49.8	大于等于 2
	衬里：水蒸气系数	毫克/平方厘米	398.8	大于等于 20
鞋垫	**SJ 抗菌防臭海波丽鞋垫**			
	脚垫：耐磨性（干/湿）（周期）	转数	25600/12800	25600/12800
大底	**聚氨酯PU/聚氨酯PU**			
	外底耐磨性（体积损耗）	毫米³	87	小于等于 150
	外底防滑性SRA：后跟	摩擦	0.30	大于等于 0.28
	外底防滑性SRA：平底	摩擦	0.32	大于等于 0.32
	外底防滑性SRB：后跟	摩擦	0.14	大于等于 0.13
	外底防滑性SRB：平底	摩擦	0.18	大于等于 0.18
	防静电值	兆欧	50.2	0.1 - 1000
	ESD值	兆欧	N/A	0.1 - 100
	后跟吸能	J	27	大于等于 20
鞋头	**-**			
	抗冲击鞋包头（冲击后间隙100J）	毫米	N/A	N/A
	抗压鞋包头（压缩后的间隙为10kN）	毫米	N/A	N/A
	抗冲击鞋包头（冲击后间隙200J）	毫米	16	大于等于 14
	抗压鞋包头（压缩后的间隙为15kN）	毫米	17	大于等于 14

样品大小：42

我们的鞋子在不断发展,所有产品名称和品牌Safety Jogger，均已注册，未经我们的书面同意，不得以任何形式使用或复制。